

MYCO TRAILERS, LLC.

Galvanized Models

Tanden Axle

Model	Boat Length	Carrying Capacity	Empty Weight	GVWR	Tire Size	Tire Capacity	Inflation Pressure
MG20-22TA	20'-22'	4,800#	1,200#	6,000#	ST215/75R14 LR-C	1,870#	50 PSI
MG23-25TA	23'-25'	4,700#	1,300#	6,000#	ST215/75R14 LR-C	1,870#	50 PSI
MG23-25TXA	23'-25'	5,500#	1,500#	7,000#	ST215/75R14 LR-C	1,870#	50 PSI
MG23-25TAX	23'-25'	7,400#	1,400#	8,800#	ST225/75R15 LR-D	2,540#	65 PSI
MG26-27TA	26'-27'	4,700#	1,300#	6,000#	ST215/75R14 LR-C	1,870#	50 PSI
MG26-27TXA	26'-27'	5,500#	1,500#	7,000#	ST215/75R14 LR-C	1,870#	50 PSI
MG26-27TAX	26'-27'	7,300#	1,500#	8,800#	ST225/75R15 LR-D	2,540#	65 PSI
MG26-27HTA	26'-27'	8,100#	1,900#	10,000#	ST235/80R16 LR-E	3,420#	80 PSI
MG28-29TAX	28'-29'	7,200#	1,600#	8,800#	ST225/75R15 LR-D	2,540#	65 PSI
MG28-29HTA	28'-29'	8,000#	2,000#	10,000#	ST235/80R16 LR-E	3,420#	80 PSI
MG28-29XHTA	28'-29'	9,900#	2,100#	12,000#	ST235/80R16 LR-E	3,420#	80 PSI
MG30-31HTA	30'-31'	7,900#	2,100#	10,000#	ST235/80R16 LR-E	3,420#	80 PSI
MG30-31XHTA	30'-31'	9,800#	2,200#	12,000#	ST235/80R16 LR-E	3,420#	80 PSI
MG32-33HTA	32'-33'	7,800#	2,200#	10,000#	ST235/80R16 LR-E	3,420#	80 PSI
MG32-33XHTA	32'-33'	9,700#	2,300#	12,000#	ST235/80R16 LR-E	3,420#	80 PSI
MG34-35XHTA	34'-35'	9,700#	2,300#	12,000#	ST235/80R16 LR-E	3,420#	80 PSI

Tri-Axle

Model	Boat Length	Carrying Capacity	Empty Weight	GVWR	Tire Size	Tire Capacity	Inflation Pressure
MG28-29HTR	28'-29'	13,200#	2,400#	15,600#	ST235/80R16 LR-E	3,420#	80 PSI
MG28-29XHTR	28'-29'	15,400#	2,600#	18,000#	ST235/80R16 LR-E	3,420#	80 PSI
MG30-31HTR	30'-31'	13,100#	2,500#	15,600#	ST235/80R16 LR-E	3,420#	80 PSI
MG30-31XHTR	30'-31'	15,300#	2,700#	18,000#	ST235/80R16 LR-E	3,420#	80 PSI
MG32-33HTR	32'-33'	13,100#	2,500#	15,600#	ST235/80R16 LR-E	3,420#	80 PSI
MG32-33XHTR	32'-33'	15,200#	2,800#	18,000#	ST235/80R16 LR-E	3,420#	80 PSI
MG34-36HTR	34'-36'	12,900#	2,700#	15,600#	ST235/80R16 LR-E	3,420#	80 PSI
MG34-36XHTR	34'-36'	15,100#	2,900#	18,000#	ST235/80R16 LR-E	3,420#	80 PSI
MG34-36XHHTR	34'-36'	17,600#	3,400#	21,000#	LT235/85R16 LR-G	3,750#	110 PSI
MG37-39HTR	37'-39'	12,900#	2,700#	15,600#	ST235/80R16 LR-E	3,420#	80 PSI
MG37-39XHTR	37'-39'	15,000#	3,000#	18,000#	ST235/80R16 LR-E	3,420#	80 PSI
MG37-39XHHTR	37'-39'	17,500#	3,500#	21,000#	LT235/85R16 LR-G	3,750#	110 PSI
MG37-39XXHTR	37'-39'	20,200#	3,800#	24,000#	235/75R17.5 LR-H	6,005#	125 PSI
MG40-42HTR	40'-42'	12,800#	2,800#	15,600#	ST235/80R16 LR-E	3,420#	80 PSI
MG40-42XHTR	40'-42'	14,900#	3,100#	18,000#	ST235/80R16 LR-E	3,420#	80 PSI
MG40-42XHHTR	40'-42'	17,300#	3,700#	21,000#	LT235/85R16 LR-G	3,750#	110 PSI
MG40-42XXHTR	40'-42'	20,000#	4,000#	24,000#	235/75R17.5 LR-H	6,005#	125 PSI
MG43-47XHTR	43'-47'	14,600#	3,400#	18,000#	ST235/80R16 LR-E	3,420#	80 PSI
MG43-47XHHTR	43'-47'	16,700#	4,300#	21,000#	LT235/85R16 LR-G	3,750#	110 PSI
MG50XXHTR	44'-50'	19,400#	4,600#	24,000#	235/75R17.5 LR-H	6,005#	125 PSI