

# MYCO TRAILERS, LLC.

## Welded Aluminum Models

### *Tandem Axle*

Model	Boat Length	Carrying Capacity	Empty Weight	GVWR	Tire Size	Tire Capacity	Inflation Pressure
MWA20-22TA	20'-22'	5,000#	1,000#	6,000#	ST215/75R14 LR-C	1,870#	50 PSI
MWA23-25TA	23'-25'	4,900#	1,100#	6,000#	ST215/75R14 LR-C	1,870#	50 PSI
MWA23-25TXA	23'-25'	5,800#	1,200#	7,000#	ST215/75R14 LR-C	1,870#	50 PSI
MWA23-25TAX	23'-25'	7,300#	1,500#	8,800#	ST225/75R15 LR-D	2,540#	65 PSI
MWA26-27TA	26'-27'	4,800#	1,200#	6,000#	ST215/75R14 LR-C	1,870#	50 PSI
MWA26-27TXA	26'-27'	5,700#	1,300#	7,000#	ST215/75R14 LR-C	1,870#	50 PSI
MWA26-27TAX	26'-27'	7,300#	1,500#	8,800#	ST225/75R15 LR-D	2,540#	65 PSI
MWA26-27HTA	26'-27'	8,400#	1,600#	10,000#	ST235/80R16 LR-E	3,420#	80 PSI
MWA28-29TAX	28'-29'	7,300#	1,500#	8,800#	ST225/75R15 LR-D	2,540#	65 PSI
MWA28-29HTA	28'-29'	8,200#	1,800#	10,000#	ST235/80R16 LR-E	3,420#	80 PSI
MWA28-29XHHTA	28'-29'	10,100#	1,900#	12,000#	ST235/80R16 LR-E	3,420#	80 PSI
MWA30-31HTA	30'-31'	8,200#	1,800#	10,000#	ST235/80R16 LR-E	3,420#	80 PSI
MWA30-31XHHTA	30'-31'	10,000#	2,000#	12,000#	ST235/80R16 LR-E	3,420#	80 PSI
MWA32-33HTA	32'-33'	8,100#	1,900#	10,000#	ST235/80R16 LR-E	3,420#	80 PSI
MWA32-33XHHTA	32'-33'	10,000#	2,000#	12,000#	ST235/80R16 LR-E	3,420#	80 PSI
MWA34-35XHHTA	34'-35'	9,900#	2,100#	12,000#	ST235/80R16 LR-E	3,420#	80 PSI

### *Tri-Axle*

Model	Boat Length	Carrying Capacity	Empty Weight	GVWR	Tire Size	Tire Capacity	Inflation Pressure
MWA28-29HTR	28'-29'	13,400#	2,200#	15,600#	ST235/80R16 LR-E	3,420#	80 PSI
MWA28-29XHTR	28'-29'	15,700#	2,300#	18,000#	ST235/80R16 LR-E	3,420#	80 PSI
MWA30-31HTR	30'-31'	13,300#	2,300#	15,600#	ST235/80R16 LR-E	3,420#	80 PSI
MWA30-31XHTR	30'-31'	15,600#	2,400#	18,000#	ST235/80R16 LR-E	3,420#	80 PSI
MWA32-33HTR	32'-33'	13,300#	2,300#	15,600#	ST235/80R16 LR-E	3,420#	80 PSI
MWA32-33XHTR	32'-33'	15,500#	2,500#	18,000#	ST235/80R16 LR-E	3,420#	80 PSI
MWA34-36HTR	34'-36'	13,200#	2,400#	15,600#	ST235/80R16 LR-E	3,420#	80 PSI
MWA34-36XHTR	34'-36'	15,400#	2,600#	18,000#	ST235/80R16 LR-E	3,420#	80 PSI
MWA34-36XHHTR	34'-36'	18,000#	3,000#	21,000#	LT235/85R16 LR-G	3,750#	110 PSI
MWA37-39HTR	37'-39'	13,100#	2,500#	15,600#	ST235/80R16 LR-E	3,420#	80 PSI
MWA37-39XHTR	37'-39'	15,400#	2,600#	18,000#	ST235/80R16 LR-E	3,420#	80 PSI
MWA37-39XHHTR	37'-39'	18,000#	3,000#	21,000#	LT235/85R16 LR-G	3,750#	110 PSI
MWA37-39XXHTR	37'-39'	20,900#	3,100#	24,000#	235/75R17.5 LR-H	6,005#	125 PSI
MWA40-42HTR	40'-42'	13,000#	2,600#	15,600#	ST235/80R16 LR-E	3,420#	80 PSI
MWA40-42XHTR	40'-42'	15,300#	2,700#	18,000#	ST235/80R16 LR-E	3,420#	80 PSI
MWA40-42XHHTR	40'-42'	17,900	3,100#	21,000#	LT235/85R16 LR-G	3,750#	110 PSI
MWA40-42XXHTR	40'-42'	20,800	3,200#	24,000#	235/75R17.5 LR-H	6,005#	125 PSI
MWA43-47XHTR	43'-47'	14,900#	3,200#	18,000#	ST235/80R16 LR-E	3,420#	80 PSI
MWA43-47XHHTR	43'-47'	17,800	3,200#	21,000#	LT235/85R16 LR-G	3,750#	110 PSI
MWA50XXHTR	44'-50'	20,500	3,500#	24,000#	235/75R17.5 LR-H	6,005#	125 PSI